



# LY?MANUFACTURING CO.,LTD.

## 4HR3065[F(AP-C),F(AP-CF),F(AP-HC)]+[146-3000/1]L THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 4HR3065[F(AP-C),F(AP-CF),F(AP-HC)]+[146-3000/1]L

4HR3065[F(AP-C),F(AP-CF),F(AP-HC)]+[146-3000/1]L Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Rail Width W1	25 mm
Mounting Height M	30 mm
Number of blocks	4
Material	Carbon Steel
Rail Length L	146 ~ 3000 mm
Accuracy Grade	Standard Grade
Callout Size	3065
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	24200
Basic Load Rating Static Rating Co(N)	38600
Allowable static moment MA(N · m)	1110
Allowable static moment MB(N · m)	1110
The outside dimension W of block	40.3 mm
The outside dimension L of block	145 mm
Mounting Hole Dimension S(M)	M10
The dimension L1 of bocks	90 mm
LM Block Surface Treatment (* Surface treatment that differs	Industrial Black Chrome Coating / Industrial Black Chrome Film Treated -



## LY?MANUFACTURING CO.,LTD.

between the rail and block or only on the rail or block is not available.)	Special Fluororesin Coating / Industrial Hard Chrome Plating
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided