



LY?MANUFACTURING CO.,LTD.

4HR3065T+[175-3000/1]L THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 4HR3065T+[175-3000/1]L

Days to Ship	42 Days
Rail Width W1	25 mm
Mounting Height M	30 mm
Number of blocks	4
Material	Carbon Steel
Rail Length L	175 ~ 3000 mm
Accuracy Grade	Standard Grade
Callout Size	3065
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	32100
Basic Load Rating Static Rating Co(N)	51600
Allowable static moment MA(N · m)	1890
Allowable static moment MB(N · m)	1890
The outside dimension W of block	40.3 mm
The outside dimension L of block	173.5 mm
Mounting Hole Dimension S(M)	M10
The dimension L1 of bocks	118.5 mm
LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block	Not Provided

4HR3065T+[175-3000/1]L Bearing 2D drawings and 3D
CAD models



LY?MANUFACTURING CO.,LTD.

is not available.)	
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided